

**Phone:** (314) 822-0500  
**24/7 Toll Free:** (800) 777-9687  
**Direct Sales Fax:** (314) 909-0131  
**Alternate Sales Fax:** (314) 821-3151

## CARBON STEEL LINE PIPE: ERW

Trident Steel represents domestic and international mills offering electric resistance welded (ERW) steel line pipe. Manufactured to API 5L specifications, our ERW line pipe is created by using high-frequency induction (HFI) currents to form a welded bond. Trident has partnered with industry-leading coating companies, offering the option for Fusion-Bonded Epoxy (FBE) coating, TGF-3 (Coal-Tar Epoxy), and other customer-specific coatings. A cost-effective option for pipe, our ERW pipe is commonly used for well hook-ups, gathering lines, tie-in lines, trunk lines, and other midstream applications. Coated, job-ready material is available for same day shipment. Our ERW pipe is available in standard, schedule 40, schedule 80 and unscheduled size options.



## CARBON STEEL LINE PIPE ERW FEATURES:

- **Available sizes:** 2 3/8 in. – 30 in. outer diameter (OD). See attached chart for a full list of dimensions.
- **Grades:** API 5L B, X42, X52, X60, X65, X70
- **Specifications:** ASTM A53-B, ASME, API-5L
- **Coating/Overlay Options:** Fusion Bonded Epoxy, TGF-3, PowerCrete / Abrasion-resistant overlay (ARO), and other customer-specific coatings
- **End Finishing:** Plain-end beveled (PEB) for welding; Zap-Lok
- **Wall Thicknesses:** Light Wall, Standard Wall, Extra Heavy and other wall thickness available

**ERW LINE PIPE DIMENSIONS AND WEIGHT: DIMENSIONS ARE IN INCHES / TOLERANCES NOT SHOWN**

OD	NOMINAL	SCHEDULE	WALL	# / FT BARE	# / FT FBE
2 3/8"	2"	Std / 40	0.154	3.66	3.73
2 3/8"	2"	80	0.218	5.03	5.1
3 1/2"	3"	Std / 40	0.216	7.58	7.68
3 1/2"	3"	80	0.3	10.26	10.36
4 1/2"	4"		0.188	8.67	8.8
4 1/2"	4"	Std / 40	0.237	10.8	10.93
4 1/2"	4"	80	0.337	15	15.13
6 5/8"	6"		0.188	12.94	13.14
6 5/8"	6"	Std / 40	0.28	18.99	19.19
6 5/8"	6"	80	0.432	28.6	28.8
8 5/8"	8"		0.188	16.96	17.22
8 5/8"	8"		0.219	19.68	19.94
8 5/8"	8"		0.25	22.38	22.64
8 5/8"	8"	Std /40	0.322	28.58	28.84
10 3/4"	10"		0.25	28.06	28.38
10 3/4"	10"	Std / 40	0.365	40.52	40.84
12 3/4"	12"		0.25	33.41	33.78
12 3/4"	12"	Std	0.375	49.61	49.99
12 3/4"	12"	XH	0.5	65.48	65.86
16"	16"		0.25	42.09	42.56
16"	16"	Std	0.375	62.64	63.11
16"	16"	XH	0.5	82.85	83.83
20"	20"	Std	0.375	78.67	79.26
20"	20"	XH	0.5	104.23	104.82
24"	24"	Std	0.375	94.71	95.42
24"	24"	XH	0.5	125.61	126.32
30"	30"	Std	0.375	118.76	127.69

**Phone:** (314) 822-0500  
**24/7 Toll Free:** (800) 777-9687  
**Direct Sales Fax:** (314) 909-0131  
**Alternate Sales Fax:** (314) 821-3151

## CARBON STEEL LINE PIPE: SEAMLESS

Trident Steel offers API 5L seamless line pipe from domestic and international mills. Seamless line pipe is manufactured by extruding metal from the center of cylindrical-shaped steel billet. The resulting hollowed out shape is seamless line pipe. Unlike ERW line pipe, there are no weld seams. Coated, job-ready material is available for same day shipment. Trident Steel's seamless line pipe is available in standard, schedule 40, schedule 80 and unscheduled size options.



### CARBON STEEL LINE PIPE SEAMLESS FEATURES:

- **Available Sizes:** 2 3/8 in. – 8 5/8 in. outer diameter (OD). See attached chart for a full list of dimensions.
- **Grades:** API 5L B through X52
- **Specifications:** ASTM A53-B, ASTM A106-B, ASME, API-5L
- **End Finishes:** Plain-end beveled (PEB) for welding, Zap-Lok
- **Coating/Overlay Options:** Fusion Bonded Epoxy, TGF-3, PowerCrete / Abrasion-resistant Overlay (ARO), and other customer-specific coatings.

**SEAMLESS LINE PIPE DIMENSIONS AND WEIGHT: DIMENSIONS ARE IN INCHES / TOLERANCES NOT SHOWN**

OD	NOMINAL	SCHEDULE	WALL	# / FT BARE	# / FT FBE
2 3/8"	2"	Std / 40	.154	3.66	3.73
2 3/8"	2"	80	.218	5.03	5.10
3 1/2"	3"	Std / 40	.216	7.58	7.68
3 1/2"	3"	80	.300	10.26	10.36
4 1/2"	4"		.188	8.67	8.80
4 1/2"	4"	Std / 40	.237	10.80	10.93
4 1/2"	4"	80	.337	15.00	15.13
6 5/8"	6"		.188	12.94	13.14
6 5/8"	6"	Std / 40	.280	18.99	19.19
6 5/8"	6"	80	.432	28.60	28.80
8 5/8"	8"		.188	16.96	17.22
8 5/8"	8"		.219	19.68	19.94
8 5/8"	8"		.250	22.38	22.64
8 5/8"	8"	Std /40	.322	28.58	28.84