

Phone: (314) 822-0500
24/7 Toll Free: (800) 777-9687
Direct Sales Fax: (314) 909-0131
Alternate Sales Fax: (314) 821-3151

OCTG CASING

Trident Steel offers OCTG casing from domestic and international mills for hydrocarbon (oil and gas) extraction. Our casing is available in variety of grades, including API J55, HCL80, HCP110 and more. Serving as the structural retainer for the walls of a drilled hole, Trident Steel offers a range of casing sizes so that customers can select the exact product for their needs. We also offer a variety of end finishes and specialties including a variety of semi-premium and premium connections. We are able to ship our casing products to any U.S. location, and we maintain stocking points in the Permian, Mid-Continent, Rockies, and Gulf Coast areas for quick delivery.



API STEEL CASING FEATURES

- **Available Sizes:** 4 1/2", 5 1/2", 7", 8 5/8", 9 5/8", 10 3/4", 13 3/8" OD.
- **API Grades:** J55, K55, N80, HCL80, HCP110, HCK55
- **End Finishing:** Plain end, ST&C, LT&C, BT&C, Semi-Premium / Drill-With-Casing Connections; Premium / Gas-Tight Connections; Flush Joint
- **Specialties:**
 - Threading
 - Heat treating
 - Drift testing (Full-length, or just ends)
 - Hydrostatic Testing
 - Full third-party inspection capabilities (EMI, SEA, and Weld Line)
 - Coating to customer specifications
 - Marker joints/Cut-to-length:

CASING SIZES AND AVAILABLE GRADES

OD	WALL	PE # / FT	T&C # / FT	COLLAR	API DRIFT	AVAILABLE GRADES
4.5"	.224	10.24	10.5	STC	3.927	J55
4.5"	.250	11.36	11.6	LTC, BTC, DWC & Premium	3.875	J55, HCL80, HCP110
4.5"	.290	13.05	13.5	LTC, BTC, DWC & Premium	3.795	HCL80, HCP110
5.5"	.244	13.71	14	STC	4.887	J55
5.5"	.275	15.36	15.5	LTC	4.825	J55
5.5"	.304	16.89	17	LTC, BTC, DWC & Premium	4.767	J55, N80, HCL80, HCP110
5.5"	.361	19.83	20	LTC, BTC, DWC & Premium	4.653	HCL80, HCP110
7"	.317	22.65	23	LTC, BTC	6.25 (OSD)	J55, HCL80, HCP110
7"	.362	25.69	26	LTC, BTC, DWC & Premium	6.151	J55, HCL80, HCP110
7"	.408	28.75	29	LTC, BTC, DWC & Premium	6.125 (OSD)	HCL80, HCP110
8.625"	.264	23.6	24	STC	7.972	J55
8.625"	.352	31.13	32	STC, LTC, BTC	7.875 (OSD)	J55
9.625"	.352	34.89	36	STC, LTC, BTC	8.765	J55
9.625"	.395	38.97	40	STC, LTC, BTC	8.750 (OSD)	J55, HCL80, HCK55
10.75"	.350	38.91	40.5	STC, BTC	9.894	J55
10.75"	.400	44.26	45.5	STC, LTC, BTC	9.875 (OSD)	J55
13.375"	.330	46.02	48	STC	12.559	J55
13.375"	.380	52.79	54.5	STC, LTC, BTC	12.459	J55
13.375"	.430	59.5	61	STC, LTC, BTC	12.359	J55
13.375"	.480	66.17	68	STC, LTC, BTC	12.259	J55

Phone: (314) 822-0500
24/7 Toll Free: (800) 777-9687
Direct Sales Fax: (314) 909-0131
Alternate Sales Fax: (314) 821-3151

OCTG TUBING

Trident Steel represents domestic and international mills, and offers a variety of grades of OCTG tubing including API J55, JFBNAU, L80, and P110. Tubing is used in drilling applications, and serves to bring hydrocarbons (oil or gas) to the surface for processing. Trident Steel's aggressive strategy of cost-control, and just-in-time delivery will help you drive down the costs associated with your completions work.

Trident Steel offers 2 3/8", 2 7/8" and 3 1/2" OD tubing, as well as macaroni tubing. We also offer a variety of grades and end finish options so that customers can select tubing that fits their needs. We can ship to any U.S. location, and maintain several stocking points in the Permian, Mid-Continent, Rockies, and Gulf Coast regions for quick delivery.



API STEEL TUBING FEATURES

- **Available Sizes:** 2 3/8", 2 7/8" and 3 1/2" Outer Diameter
- **Macaroni Tubing:** 1 1/4 " – 2 1/16" Nom.
- **Grades:** J55, J55-FBNAU, N80, L80, P110
- **End Finishing:** External Upset Ends (EUE), PH6 (and equivalent connections), Flush Joint, Integral Joint (IJ)
- **Specialties:**
 - Threading
 - Heat treating
 - External upset
 - Drifting (Full-length, or just ends)
 - Hydrostatic Testing
 - Full third-party inspection capabilities (EMI, SEA, and Weld Line)
 - Couplings – EUE, AB Modified, turned down, special clearance couplings
 - Coating to customer specifications
 - Pup Joints

TUBING SIZES AND AVAILABLE GRADES

OD	WALL	PE # / FT	T&C # / FT	COLLAR	API DRIFT	AVAILABLE GRADES
2.375"	.190	4.44	4.7	EUE, AB MOD	1.901	J55, J-FBNAU, N80, L80, P110
2.875"	.217	6.17	6.5	EUE, AB MOD	2.347	J55, J-FBNAU, N80, L80, P110
3.5"	.254	8.81	9.3	EUE, AB MOD	2.867	J55, J-FBNAU, N80, L80, P110